

Specifications																											
		Lift(m)			Wira	Hoisting						Traversing															
Туре				Wire rope			Hoisting					Mono-rail · Low hearoom						Double-rail									
	Capacity(t)			Mo	Dor Lov	- D				Motor						Motor							Motor		r		
				Monorail type	Double rail type Low head type	Rope specification	Speed m/s (m/min)		Output (kW)		Rated Current (A)		Poles	m	Speed m/s (m/min)		Output (kW)		Rated Current (A)		Speed m/s (m/min)		Output (kW)		Rated Current (A)		Poles
		Low	High	2 falls	4 falls	ion	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz		50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz		50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	
R *1 F	1	2 6	12	φ 8 **1	ф 6.3	6×W(19) B class JIS-G3525	0.112 (6.7)	0.133	1.2	1.4	7.4	7.9				0.22	0.26	1.6	1.5	4		_	_	_	_	_	
	2			φ 10	φ 8		1001	0.12 (7,2)	2.2	2.6	13.1	13.2		0.35	0.417 (25)	0.5	0.0	0.0	3.1			_	_	_	_	_	_
	2.8			φ 12.5	φ 9				3	3.6	19	19.4				0.5	0.6	3.2			0.35 0.4 (21) (2	0.417	0.5	0.6	3.2	3.1	4
	3			φ 12.5	φ 9				3.2	3.8												(25)					
	3		cation	φ 12.5	φ 9		(-7)				19	19.4									0.35 (21)	0.417 (25)	0.5	0.6	3.2	3.1	

Note 1: High lift models (Low-head type1~2.8t,Double rail type2.8t)are not available.

●Power supply···3-phase 200V 50/60Hz control 200V, 220V 60Hz control 220V (400V class is also available)···3-Phase 400V 50/60Hz control 200V, 440V 60Hz control 220V 3-Phase 380V 50Hz control 48V (100V and 24V are also abailable)

●Operating method···Push button switch operations.

	1/2~3t
Suspended type	2 Points
Frame mounted type	UD
Motor operated traversing hoist	6 Points
wotor operated traversing noist	UDEWSN

Standard specifications

- specifications ●Rating…30 min. (JIS C 9620)
 - ●Power supply system···Both trolley feeding and cable feeding are available. Howeve, neither trolley nor cable is attached.
 - ●Enclosure···Simplified outdoor type(JISC 0920, Equivalent to IP44)

(Rainproof cover is required, when it is used in the open air.)

- Applicable standard…JIS C 9620 electric hoist/crane structure standard
- ●Color coating··· Main body:Metallic gray (Equivalent to MunsellN4.0)

Hook block:Munsell 7.5YR7/14

Pushbutton: Equivalent to Munsell 7.5YR7/14

- ●Ambient air temperature···-10°C to 40°C (Non congelation)
- Ambient relative humidity…90% or less (Non condensing)

Note:These hoists cannot be used for lift (elevator for passengers.)