Mitsubishi hoist

Sales & Service

No. 855-0329

Supply of service parts for old type hoist (Notice)

We would like to thank you for your continued support of our products and wish your continued success and prosperity. Regarding the hoist roughly 30 years passed after the discontinuation of production, we have been supplying service parts for mainly on consumables; however, it is expected that it becomes impossible to continuously supply the same manner in the near future. Therefore, we would like to contact you the service deadline of the service parts shown below and kindly confirm the content accordingly. We appreciate for your consideration by all means and hoping to replace the existing product to the current product in the near future.

1. Subject model (Newly Added Models)

HY-A-VT-O~⑤ and VS-O~⑤type (Excluding -⑥type) Capacity: 7.5t or more
U-Z series

2. Service deadline

We will end all of service parts production with the order received on March 2023.

(The shipment will be arranged until the end of September 2023)

Please be informed that supply may be terminated before above deadline.

3. Requested matter

- (1) The above products have already exceeded the design life of the product, and it is time to replace the product accordingly. Please consider updating to the current product in the near future.
- (2) There are increase in number of service parts that cannot be supplied and cases where we may ask you to withdraw the sales quotation accordingly. (Example: Parts produced by mold, etc.)

 Please request sales quotation to us case by case basis.
- (3) Based on basic operation, service parts supply period for hoist and related equipment (saddles, etc.) is 11 years after the production is discontinued. We do our very best to supply service parts as much as possible; however, point of view in a variety of status quo, such as low frequency usage by the user that we cannot continue to supply service parts due to parts with little order record or deterioration of molds. Please contact regarding production that has been discontinued for 11 years.
- (4) Some models that have finished supplying the service parts and there are shared parts based on the supplied models; however, for models that have finished supplying the service parts, warranty will not be covered including the service parts.
 - * Attachment: Mitsubishi Hoist & Related Device Model Change History

j,	Supply of service parts	Date of issue	December, 2020
Subject	for old type hoist (Notice)		INDUSTRIAL PRODUCTS CORPORATION Nishi-ku, Fukuoka 819-0192

3-1 Mitsubishi Hoists & Related Device Model Change History

									3-1																													
Model	Capacity		'54	to '69		'7(0 '71	'72	'73 '7	74 '75	'76	77 78	3 '79	'80	'81 '8	32 '83	'84	'85 '8	36 '87	'88 '89	9 '9(0 '91 '			'96 '97 '9									10 '11		'13 '1	4 '15	'16
≗∣	Capacity		S29	to S44		S4:	5 S46	S47	S48 S	49 S50	S51 S	S52 S5	3 S54	S55 S	S56 S	57 S58	S59	S60 S	61 S62	S63 H0	1 H0	02 H03 F	104 H05 H)6 H07	H08 H09 H1	0 H11 F	12 H13	H14 H	I15 H16 F	117 H1	18 H19	H20 H	121 H	22 H23	H24 I	H25 H	26 H27	H28
П	1/4	HN-1/4,F	IN-1/4B	,HN-1/4D				H	N-1/4E		Ĭ	HY-	1/4A										J	1/4)	Pi	roduct	tion dis	conti	nued in	June	, 2003	3.	
ا ؞	1/2	HR-1/2 ·	A.HN-1/	2,HN-1/2E	3.HN-1/2	D D		H'	N-1/2E		Ť		H)	′-1/2A						S-1/2									S-	1/2-2		-						
[1			-1,HB-1B	-	┰					T	IY-1A	_	HY-1		Ť				S-1										S-1-2								一
: 1	2			-2,HB-2B		┢			1Y-2		÷	1/1	\equiv	/-2A	7,7,2	-				S-2	-									6-2-2			_			_		뻭
ŀ				-3,HB-3B		╬			1Y-3		+	_		-2.8A	_	-		2.8	Ϋ́		S-2.	0 0						_		2.8-3	_		_		_	_		一
ŀ	3			-3,00-30		╌	D D			_	-	_	- 1111				3-2	2.0	Ц			.0-2				0.5.6		_		70-3			_	0.5.0	_	_		=
ŀ	5	HB-5,HB				벁	B-5D	7	HY-		Щ,			HY-5							5-5		Y	<u></u>		S-5-2								S-5-3				=
ŀ	7.5	HB-7.5,⊦				_ _			1Y-7.5				_			7.5A									IY-7.5A-6	ļ.,					S-7							
L	10	HB-10,H	B-10B			┸		$\overline{}$	HY-10							-10A				\sim	~		HY-10A	\rightarrow	HY-10A-6						S-	10						
L	15	HB-15,H	B-15B					<u> </u>	HY-15		I				HY-	-15A				15A-3	(HY	Y-15A-4	HY-15A	5 I	HY-15A-6)(S-	15						=
I	20	HB-20B						F	HY-20						HY	-20A				20A-3	(HY	Y-20A-4	HY-20A	5 I	HY-20A-6						S-	20						
Γ	30							F	HY-30						HY	-30A				30A-3	HY	Y-30A-4	HY-30A	5 I	-1Y-30A-6						S-	30						
3	1							Н	E-1		H	E-1A		HE-1	A-2					R-1			R-1-	2						R-1-3	-							
Š	2					▝		H	IE-2		Ĥ	E-2A		HE-2	PA-2	Ŷ				R-2			R-2-							R-2-3								
≱ †	3				+	╁			E-3		==	E-3A		HE-3		Ť				R-2.	8			\Rightarrow						3-2, 8-								\dashv
şŀ	5 to				+	┰		Ħ	Ť		ΤÏ	- 5/1	\top		5A to	30A	\Box			112.	Ť			\top					T	, 5-	_		Т		١	_	M-5	=
ďŀ	10 to	\vdash		+ +	++	+	+	+	+	-	++	+	+-	1112-0	JA 10	JUA	+		+	 	+	+	+	+		++	+	+	+	+	+	++	+	+	-		M-10	=
+		1114/40		++-	++	+	+	+-+		1/10	 	_	+	\vdash	+	+	+		+		+	++	+	+		++	+	-	+	_	+	++	+	+			101-10	\blacksquare
gŀ	1/10	HJ-1/10			+	+	<u> </u>			-1/10E	=				_	1/7.0				\bot	\perp					\perp		F 4 (=										\bot
₽.	1/7	HW-1/10		+	++	⊣⊨	HL-1			L-1/7E	==					1/7A				-	_							E-1/7					_					=
힑.	1/4	HJ-1/5			\perp	┵	HL-1			IL-1/4E	=					1/4A				-	_							E-1/4										
흸.	1/2	HJ-1/2B		\perp		┵	HL-1	1/2		IL-1/2E	<u> </u>					1/2A											\rightarrow	E-1/2										
ĬĘ	1	HJ-1B			$\perp \perp$	_ _	_									HL-1/	A				_					HĻ-	1A-M2			P	roduc	tion dis	scont	inued in	Octo	ober 2	003.	
⅃	2	HJ-2B				\perp		Ш		\perp					Н	L-2A																						
П	1/7 to 1/2																				Т						UE	Туре							Product	tion disco	ontinued in	in April 2
Γ	1 to 2.8					Т		П						П							Т										UF	≀ Type				_		
ı	3t or lower							П												i i	1													U2	_			$\overline{}$
<u> </u>	5t							\Box										Π ,	J-K	U-KZ		U-	Z		U	I-Type (In	telligent)			ı			Е	XCELLE	NT			
₫	7.5t or higher					+		\Box	-																									U2. HU	2			一
⁼ ŀ	ligh-speed type			+		+		+	-									\vdash			╅		\top		U,	HU Type	s (Intellige	ent)						U2, HU EXCELLE				
H	5t					+	+	\rightarrow	\rightarrow	_	+	_			_	_	+ +		_	_	+	++											\neg				UM-5	
- }	10t			e frequenc nly model)	y types	\vdash	+	+	+	+	+	+	+	\vdash	+	+	+		+		+	+	+	+	++	++	+	+	+	+	+	+	+	+	+		UM-10	
ᆔ		,0000	- 243 01	,		+	+	+	+	-	++	-	+	\vdash	-	1157	A 1/-	-			_		\perp		$\perp \perp \perp$		/O tr. 5	/T	\perp			\perp					UIVI-1	14
ğ.	to 5	\vdash		+	++	+	+	\vdash	\rightarrow	-	+	_	-	\vdash	-	(HY	-A-VT									S-1	/2 to 5-\	V I					_					=
ŝ	7.5 to	\vdash	_	+	++	+-	\perp	لبل					\perp	لبيا				_			HY.	′-A-VT		_		٠.		_			S-	-VT	_					_
Į.	1/4	$\sqcup\sqcup$			\perp	4			F-1/4-H		_		_	HF-1/4							_						-1/4-HF						_					
엹.	1/2	HN-1/2B				ļĻ			F-1/2-h				$\overline{}$	HF-1/2							_					S	-1/2-HF											
ğ	1	HN-1B-H	IF					H	IF-1-H					HF-1/				S-1-HI									S-1-H	IF2										
T			0.2	0	\Box			\perp			\Box				ST-0	0.2A				ST-0.2D		ST-).2D2						S	T-0.2E	03							
1			0.4	0			ST-2	[ST-0.4	S	T-0.4E				ST-0	0.4A				ST-0.4D		ST-).4D2						S	T-0.4E	03							
1			0.4	0		T									ST-0	.4A-L			S	Γ-0.4D2-	L	ST-0	.4D3-L	Ť					ST	-0.4D	4-L							
-			0.7	5		[ST-3	s	T-0.75	i s	T-0.75	3)[•	ST-0	.75A			ÎS	ST-0.75D)	ST-0	.75D2						ST	-0.75	D3							Ti-
- [Standa	rd 0.7	5	+	┪	T		\top	T-	ΠÍ					75A-W	_		_~	Γ-0.75D-V	=		75D2-W	┿						0.75D								T
1	Top-running		0.7	5	+	+		+	+			\top	1	\Box		1				·		- J	D2	⇟						0.75D								=
3	type		1.5			1	ST.5	_	ST-1.5	<u> </u>	T-1 55	aH	-	\vdash	-	_	+		_		+	+	1	┰					1	0.700			Т					\top
š	,,,,,,		2.2		\perp		01-0		<u>≥11.5</u>	_ 13	<u> </u>	+ د	+	\vdash	-	+	+				_				\vdash		ST-2.:	3D /4/									\perp	╁
Ci al le saudie			0.4	I ne tollo	ving types a				30)		+	-	+	\vdash	+	+	+	CT 1	1467	OT 0 40		OT A "	20 11 110	+			91-2.	2D-41		4D0 '	1 110				_			=
i			_		pe (electron (mechanic						\vdash	_	-	\vdash	-	_	+	(51-(J.4A	ST-0.4D	+	51-0.41	02-U, UC	+						4D3-l								-
- [Without r	ails 0.4	TIB type	(travel inver	ter contr	rol panel)				\vdash		_	\vdash	_		\sqcup				\bot		\perp	ightharpoons						0.4D3								
- 1			0.7	Droductio	indicated in n of SC-A T			tinued !-	Contor-	nor 2004	\sqcup			\sqcup	\perp		\sqcup	ST-0	.75A S	ST-0.45E) [ST-0.75	D2-U, UC	\perp					ST-0.			,						
- 1			0.7	5 L FIOUDCIO	11 JI JU-A I	-		_	_								\perp				\perp									.75D3	_							
			0.2	0		G	SP-1	E	SP-0.2	Ţs	P-0.2E				SP-	0.2A				SP-0.2D		SP-	0.2D2						S	P-0.2E	03							
}			0.4	0			SP-2	5	SP-0.4	S	P-0.4E				SP-	0.4A				SP-0.4D		SP-).4D2						S	P-0.4E	03							
-	Suspens	sion type		-			SP-3	S	P-0.75	S	P-0.75	B) T							T		Т						\top				\top		T		\equiv			\Box
	Suspens	sion type	0.7	b	1 1		יוכ	, 0					-	-	-	_	+ +	$\overline{}$			-	\rightarrow						- 1		- 1				1 1	- 1			
	Suspens	sion type	_			_		_		2											1			\neg		+			+		+	++	+		\dashv	+	+	
	Suspens	sion type	0.2	0		0	.26B	S	GM-0.2					GM-0	4B			T			SGM	I-O 4 A		$\overline{}$					90	M-0 4	ΙΔ2		#					Щ
	Suspens Crane sac		0.2	0		0	.26B 0.5B	SC	GM-0.2	4				GM-0				Į			_	1-0.4A								iM-0.4			#					
		ddle	0.2 0.4 0.7	0		0	0.26B 0.5B 1.0B	SC	GM-0.2 GM-0.4	4 T			S	GM-0.	75B			Į		S	GM-	-0.75A							SG	M-0.7	5A2		‡ •					
	Crane sad	ddle n motor	0.2 0.4 0.7 1.5	0 0 5		0	.26B 0.5B	S(S(S(GM-0.2 GM-0.4 GM-0.7	4 I 7 I 5 I			S	GM-0.	75B .5B			Ţ		S	GM-								SG		5A2							
	Crane sad	ddle n motor	0.2 0.4 0.7	0 0 5 0		0	0.26B 0.5B 1.0B	S(S(S(GM-0.2 GM-0.4	4 I 7 I 5 I			S	GM-0.	75B .5B			Į Į		S	GM-	-0.75A					SGM-2.		SG	M-0.7	5A2							